

Batteries Industrielles

**TECH
POWER**

INDUSTRY

**TECH
POWER**
INDUSTRY

Une gamme complète couvrant les besoins d'un maximum de domaines d'applications



**TECH
POWER**
INDUSTRY

TPC12
12V 8.8Ah

Caution:

- Read out of reach of children
- Do not expose to flames or spark
- Do not short circuit battery terminals
- Do not charge in gas tight container
- Do not disassemble or drop
- Always charge after use in a well ventilated area
- Do not attempt to charge if battery becomes hot
- Do not expose case to organic solvents
- Contains dilute sulfuric acid. If physical contact with liquid, flush immediately with water and seek medical attention.

Risk of fire, explosion, or burns. Do not disassemble, heat above 65°C, or incinerate.
RECYCLABLE Rechargeable VRLA Battery MUST BE RECYCLED in Vietnam

**TECH
POWER**
INDUSTRY

TPG12-35
12V 35Ah

Caution:

- Keep out of reach of children
- Do not expose to flames or spark
- Do not short circuit battery terminals
- Do not charge in gas tight container
- Do not disassemble or drop
- Always charge after use in a well ventilated area
- Do not attempt to charge if battery becomes hot
- Do not expose case to organic solvents
- Contains dilute sulfuric acid. If physical contact with liquid, flush immediately with water and seek medical attention.

Risk of fire, explosion, or burns. Do not disassemble, heat above 65°C, or incinerate.
RECYCLABLE Rechargeable VRLA Battery MUST BE RECYCLED in Vietnam

GEL TECHNOLOGY
Rechargeable Valve Regulated Lead Acid Battery
NONSPILLABLE

Charging Restrictions(5°C - 35°C)

| APPLICATION | Voltage Regulation | Initial Current |
|-------------|--------------------|-----------------|
| Standby Use | 13.58 - 13.98 | 0.3 CAPACITY |
| Cycled Use | 14.48 - 15.98 | 0.3 CAPACITY |



Rechargeable Battery, in accordance with IEC609
13.58 and 15.98, is not restricted for air transport.
Complies with IATA/ICAO Special Provision A67.

www.proxitech.com



TP



Les batteries, de type UPS (alimentation non interrompible), sont conçues pour les applications de floating (appareils restant perpétuellement en charge) ou de cyclage (charge et décharge peu profondes). Elles répondent à une technologie AGM et sont 100% étanches.

TPC



Batterie de cyclage, hautes performances, qui supporte les décharges profondes. Batteries conçues pour être déchargées et rechargées très souvent. Résistance aux vibrations. Technologie AGM, 100% étanche.

TPG



Pour cette technologie, l'électrolyte est immobilisée sous forme de Gel. Les batteries Gel ont une durée de vie plus longue et une meilleure résistance aux cyclages. Technologie GEL, 100% étanche.

Stationnaires TP (UPS)

| TECHPOWER Réf : | LEOCH | YUASA | V | Ah/ C20 | Dimensions L x l x h | Haut. bornes incl. | Type de borne | Polarité |
|-----------------|----------------------|-----------|----|---------|----------------------|--------------------|---------------|----------|
| TP6-1.3 | LP6-1.2 | NP1.2-6 | 6 | 1,3 | 97 x 25 x 52 | 57 | F1 | G |
| TP6-3 | LP6-3.2 | NP2.8-6 | 6 | 3 | 134 x 34 x 59 | 65 | F1 | G |
| TP6-4.5 | LP6-4.0 | NP4-6 | 6 | 4,5 | 70 x 47 x 101 | 107 | F1 | G |
| TP6-7 | LP6-7.0 | NP7-6 | 6 | 7 | 151 x 34 x 94 | 100 | F1 | G |
| TP6-12 | LP6-12 | NP10-6 | 6 | 12 | 151 x 50 x 94 | 100 | F2 | G |
| TP12-1.3 | LP12-1.2 | NP1.2-12 | 12 | 1,3 | 97 x 43 x 53 | 59 | F1 | G |
| TP12-2.3 | LP12-2.3 | NP2.1-12 | 12 | 2,2 | 178 x 34 x 60 | 66 | F1 | G |
| TP12-2.9 | LP12-2.9 | - | 12 | 2,9 | 79 x 56 x 101 | 107 | F1 | D |
| TP12-3.5 | LP12-3.2 | NP2.8-12 | 12 | 3,6 | 134 x 67 x 60 | 66,5 | F1 | G |
| TP12-5 | LP12-4.5 LP12-5.4 | NPH5-12 | 12 | 5,8 | 90 x 70 x 101 | 107 | F1 | G |
| TP12-7.0 | LP12-7.0 | NP7-12 | 12 | 7 | 151 x 65 x 94 | 102 | F2 | G |
| TP12-7.2 | LP12-7.2 | NP7-12 | 12 | 7,2 | 151 x 65 x 94 | 102 | F2 | G |
| TP12-12 | LP12-12 | NP12-12 | 12 | 12 | 151 x 98 x 93 | 98 | F2 | D |
| TP12-20 | LP12-20 | NP17-12 | 12 | 20 | 181 x 76 x 167 | 167 | F3 | D |
| TP12-26 | LP12-26 | NPL24-12 | 12 | 26 | 166 x 175 x 125 | 125 | F8 | D |
| TP12-40 | LP12-38 | NP38-12 | 12 | 40 | 197 x 165 x 170 | 170 | F8 | D |
| TP12-45 | LP12-45 | SWL1100 | 12 | 48 | 197 x 165 x 170 | 170 | F8 | D |
| TP12-55 | LP12-55 | SWL1800 | 12 | 60 | 229 x 138 x 205 | 229 | F14 | G |
| TP12-100 | LP12-100 | NPL100-12 | 12 | 110 | 330 x 174 x 217 | 238 | F8 | G |

Stationnaires Deep Cycle TPC

| TECHPOWER Réf : | LEOCH | YUASA | V | Ah/ C20 | Dimensions L x l x h | Haut. bornes incl. | Type de borne | Polarité |
|-----------------|----------|----------|----|---------|----------------------|--------------------|---------------|----------|
| TPC12-8.5 | LPC12-8 | - | 12 | 8,8 | 151 x 65 x 94 | 100 | F2 | G |
| TPC12-13 | LPC12-13 | - | 12 | 13 | 151 x 98 x 93 | 98 | F2 | D |
| TPC12-22 | LPC12-20 | NPC17-12 | 12 | 22 | 181 x 76 x 172 | 172 | F3 | D |
| TPX12-22 | LPX12-20 | - | 12 | 22 | 181 x 76 x 172 | 172 | F8 | D |

Stationnaires Deep Cycle TPG

| TECHPOWER Réf : | LEOCH | YUASA | V | Ah/ C20 | Dimensions L x l x h | Haut. bornes incl. | Type de borne | Polarité |
|-----------------|-----------|----------|----|---------|----------------------|--------------------|---------------|----------|
| TPG12-28 | LPG12-26 | NPC24-12 | 12 | 28 | 166 x 175 x 125 | 125 | F8 | G |
| TPG12-35 | LPG12-31 | - | 12 | 35 | 197 x 130 x 159 | 170 | F4 | G |
| TPG12-50 | LPS12-50 | - | 12 | 50 | 197 x 165 x 170 | 170 | F8 | D |
| TPG12-55 | LPG12-50 | - | 12 | 60 | 230 x 138 x 205 | 205 | F8 | G |
| LPCG12-60S | LPCG12-60 | - | 12 | 60 | 260 x 174 x 179 | 179 | F8 | D |
| TPG12-75 | LPG12-70H | - | 12 | 80 | 259 x 168 x 208 | 208 | F8 | G |
| TPG12-90 | LPG12-85 | - | 12 | 95 | 305 x 168 x 208 | 208 | F11 | G |
| TPG12-100 | LPG12-100 | - | 12 | 100 | 330 x 174 x 217 | 217 | F11 | G |
| TPG12-135 | LPG12-135 | - | 12 | 135 | 340 x 173 x 281 | 281 | F8 | G |

Batteries pour boosters


| TECHPOWER Réf : | LEOCH | V | Ah/ C20 | A/EN | Dimensions L x l x h | Haut. bornes incluses | Bornes | Poids (kg) | Polarité |
|-----------------|----------|----|---------|------|----------------------|-----------------------|--------|------------|----------|
| TPC12-22 | LPC12-20 | 12 | 22 | 330 | 181 x 77 x 172 | 172 | F3 | 6,2 | D |
| TPX12-22 | LPX12-20 | 12 | 22 | 500 | 181 x 77 x 172 | 172 | F8 | 7,2 | D |

Domaines d'applications

- ✓ Informatique
- ✓ Data center / Réseaux télécoms
- ✓ Équipement médical
- ✓ Alarmes
- ✓ Sécurité et détection incendie
- ✓ Robotique et automatisme
- ✓ Équipements maritimes
- ✓ Équipements ferroviaires
- ✓ Systèmes éoliens, solaires.


Bornes

F1




Fastom

F2




Langnette

F3




Langnette

F4




Langnette

F8




Insert 06 mm

F11




Insert 08 mm

F14



BRB61



Kit 2 bornes 08 mm

Scannez-moi !



www.proxitech.com